





All furnished with exhaust conn.



8 and 10-inch

Bench and Pedestal Grinders

Alternating Current — Direct Current

Order by Type, Current and Volts. If Alternating Current, Give Cycles and Phase.

POWERFUL Ball-Bearing Grinders with repulsion induction motors, which are safely recommended for grinding of all kinds and for general purpose buffing and polishing. Fully enclosed safety wheel guards with exhaust connections. Grinding rests and spark shields are adjustable to wear of wheels. Ball bearings are mounted in dust-proof housings in closest proximity to grinding wheels. They are correctly locked to the shaft to provide end thrust and eliminate shaft wear. Two-pole starting switch is entirely enclosed in the base of the motor. Shatter-proof glass eye shields, flexible light arms and twist drill grinding attachment furnished as extras, see page 10.

EQUIPMENT—Two grinding wheels, wheel guards and grinding rests. Rubber-covered cable with attachment plug, furnished on single phase grinders only.

ALTERNATING CURRENT SPECIFICATIONS

Type	Volts	H. P.	Load Speed, R. P. M.	Wheel Size	Diam. Shaft Bet. Flanges	Distance Bet. Wheels and Height to Center of Spindle	Size of Base at Bottom	Net Weight, Pounds	Shipping Weight, Pounds	Code Word
BHA-Bench	110-60-1	1/2	3400	8" x 1"	5/8"	18" x 7 1/4"	10" x 9"	120	160	FLORAL
*BHA-Bench	220-60-1	1/2	3400	8" x 1"	5/8"	18" x 7 1/4"	10" x 9"	120	160	FLORET
BLA-Bench	110-60-1	1	1750	10" x 1"	3/4"	18" x 7 1/4"	10" x 9"	145	190	FAGIN
*BLA-Bench	220-60-1	1	1750	10" x 1"	3/4"	18" x 7 1/4"	10" x 9"	145	190	FAMA
FHA-Peds'l	110-60-1	1/2	3400	8" x 1"	5/8"	18" x 39"	16" x 12"	210	315	HANSON
*FHA-Peds'l	220-60-1	1/2	3400	8" x 1"	5/8"	18" x 39"	16" x 12"	210	315	HANDY
FLA-Peds'l	110-60-1	1	1750	10" x 1"	3/4"	18" x 39"	16" x 12"	260	330	FANAR
*FLA-Peds'l	220-60-1	1	1750	10" x 1"	3/4"	18" x 39"	16" x 12"	260	330	FANON

*Can also be furnished for 220, 440 or 550 volts, 2 or 3 phase, regular list price. Speed for 25 cycles, 1500 R.P.M. For other than 50 or 60 cycles, see price sheet.

DIRECT CURRENT SPECIFICATIONS

BH-Pench	115	1/2	3400	8" x 1"	5/8"	18" x 7 1/4"	10" x 9"	120	160	FLASH
BH-Bench	230	1/2	3400	8" x 1"	5/8"	18" x 7 1/4"	10" x 9"	120	160	FLEDGE
BL-Bench	115	1	1750	10" x 1"	3/4"	18" x 7 1/4"	10" x 9"	150	190	FABRE
BL-Bench	230	1	1750	10" x 1"	3/4"	18" x 7 1/4"	10" x 9"	150	190	FADGE
FH-Pedestal	115	1/2	3400	8" x 1"	5/8"	18" x 39"	16" x 12"	210	315	GRANNY
FH-Pedestal	230	1/2	3400	8" x 1"	5/8"	18" x 39"	16" x 12"	210	315	GLASS
FL-Pedestal	115	1	1750	10" x 1"	3/4"	18" x 39"	16" x 12"	260	330	FAUM
FL-Pedestal	230	1	1750	10" x 1"	3/4"	18" x 39"	16" x 12"	260	330	FAIK

You should have an AIR MASTER with this Tool, see page 47.